

# ActuateOne™

One Design  
One Server  
One User Experience

## Installing an Actuate Java Component

Information in this document is subject to change without notice. Examples provided are fictitious. No part of this document may be reproduced or transmitted in any form, or by any means, electronic or mechanical, for any purpose, in whole or in part, without the express written permission of Actuate Corporation.

© 1995 - 2011 by Actuate Corporation. All rights reserved. Printed in the United States of America.

Contains information proprietary to:  
Actuate Corporation, 2207 Bridgepointe Parkway, San Mateo, CA 94404

[www.actuate.com](http://www.actuate.com)  
[www.birt-exchange.com](http://www.birt-exchange.com)

The software described in this manual is provided by Actuate Corporation under an Actuate License agreement. The software may be used only in accordance with the terms of the agreement. Actuate software products are protected by U.S. and International patents and patents pending. For a current list of patents, please see <http://www.actuate.com/patents>.

Actuate Corporation trademarks and registered trademarks include:  
Actuate, ActuateOne, the Actuate logo, BIRT, Collaborative Reporting Architecture, e.Analysis, e.Report, e.Reporting, e.Spreadsheet, Encyclopedia, Interactive Viewing, OnPerformance, Performancesoft, Performancesoft Track, Performancesoft Views, Report Encyclopedia, Reportlet, The people behind BIRT, and XML reports.

Actuate products may contain third-party products or technologies. Third-party trademarks or registered trademarks of their respective owners, companies, or organizations include:

Adobe Systems Incorporated: Flash Player. Apache Software Foundation ([www.apache.org](http://www.apache.org)): Axis, Axis2, Batik, Batik SVG library, Commons Command Line Interface (CLI), Commons Codec, Derby, Shindig, Struts, Tomcat, Xerces, Xerces2 Java Parser, and Xerces-C++ XML Parser. Bits Per Second, Ltd. and Graphics Server Technologies, L.P.: Graphics Server. Bruno Lowagie and Paulo Soares: iText, licensed under the Mozilla Public License (MPL). Castor ([www.castor.org](http://www.castor.org)), ExoLab Project ([www.exolab.org](http://www.exolab.org)), and Intalio, Inc. ([www.intalio.org](http://www.intalio.org)): Castor. Codejock Software: Xtreme Toolkit Pro. DataDirect Technologies Corporation: DataDirect JDBC, DataDirect ODBC. Eclipse Foundation, Inc. ([www.eclipse.org](http://www.eclipse.org)): Babel, Data Tools Platform (DTP) ODA, Eclipse SDK, Graphics Editor Framework (GEF), Eclipse Modeling Framework (EMF), and Eclipse Web Tools Platform (WTP), licensed under the Eclipse Public License (EPL). Jason Hsueth and Kenton Varda ([code.google.com](http://code.google.com)): Protocole Buffer. ImageMagick Studio LLC.: ImageMagick. InfoSoft Global (P) Ltd.: FusionCharts, FusionMaps, FusionWidgets, PowerCharts. Mark Adler and Jean-loup Gailly ([www.zlib.net](http://www.zlib.net)): zlib. Matt Ingenthron, Eric D. Lambert, and Dustin Sallings ([code.google.com](http://code.google.com)): Spymemcached, licensed under the MIT OSI License. International Components for Unicode (ICU): ICU library. KL Group, Inc.: XRT Graph, licensed under XRT for Motif Binary License Agreement. LEAD Technologies, Inc.: LEADTOOLS. Microsoft Corporation (Microsoft Developer Network): CompoundDocument Library. Mozilla: Mozilla XML Parser, licensed under the Mozilla Public License (MPL). MySQL Americas, Inc.: MySQL Connector. Netscape Communications Corporation, Inc.: Rhino, licensed under the Netscape Public License (NPL). Oracle Corporation: Berkeley DB. PostgreSQL Global Development Group: pgAdmin, PostgreSQL, PostgreSQL JDBC driver. Rogue Wave Software, Inc.: Rogue Wave Library SourcePro Core, tools.h++. Sam Stephenson ([prototype.conio.net](http://prototype.conio.net)): prototype.js, licensed under the MIT license. Sencha Inc.: Ext JS. Sun Microsystems, Inc.: JAXB, JDK, Jstl. ThimbleWare, Inc.: JMemcached, licensed under the Apache Public License (APL). World Wide Web Consortium (W3C)(MIT, ERCIM, Keio): Flute, JTIty, Simple API for CSS. XFree86 Project, Inc.: ([www.xfree86.org](http://www.xfree86.org)): xvfb.

All other brand or product names are trademarks or registered trademarks of their respective owners, companies, or organizations.

Document No. 110303-2-781510 March 1, 2011

# Contents

<b>Introduction</b> .....	<b>.iii</b>
Understanding ActuateOne .....	iii
About Actuate Java Component documentation .....	iii
Obtaining documentation .....	v
Obtaining late-breaking information and documentation updates .....	vi
Using PDF documentation .....	vi
About obtaining technical support .....	vi
About supported and obsolete products .....	vi
Typographical conventions .....	vii
Syntax conventions .....	vii
About <i>Installing an Actuate Java Component</i> .....	viii
<b>Chapter 1</b>	
<b>Before you begin</b> .....	<b>1</b>
About Actuate Java Components .....	2
About deployment formats .....	2
Checking installation prerequisites .....	3
About the license key file .....	3
<b>Chapter 2</b>	
<b>Deploying a Java Component</b> .....	<b>5</b>
Editing the web.xml file .....	6
Configuring locale parameters .....	7
Configuring parameters for Deployment Kit .....	7
Configuring parameters for BIRT Viewer and BIRT Interactive Viewer .....	8
Configuring parameters for BIRT Studio .....	8
Compressing files and renaming the WAR file .....	9
Deploying the WAR file .....	9
<b>Chapter 3</b>	
<b>Using a Java Component</b> .....	<b>11</b>
Testing the installation .....	12
Using Java Components .....	12
Using BIRT Viewer and BIRT Interactive Viewer .....	12
Using BIRT Studio .....	13
Using the Deployment Kits .....	13
Licensing a Java Component in a WAR file .....	15
Setting JVM properties .....	16
<b>Index</b> .....	<b>19</b>



---

## Understanding ActuateOne

ActuateOne™ includes Release 11 of Actuate® Corporation's value-added products for the Eclipse BIRT open source project. ActuateOne institutes a paradigm shift in Business Intelligence technology from individualized tools to a suite of integrated capabilities within a single environment. ActuateOne is one designer, one server, one integrated environment providing a single unified user experience. A common architecture is precisely what today's information-rich global environment requires for development and deployment. This unified Actuate technology continues to enable information management and delivery while supporting advanced security, massive scalability, flexibility through programming, and reuse. ActuateOne realizes our corporate vision of a single user experience by providing extended new analytics capabilities reaching a broader spectrum of users. The new dashboard functionality supports building gadgets to enhance the visual presentation of information. Export to Excel® and other formats integrates Actuate output with other tools on the end-user desktop. Actuate's cloud-ready server supports elastic clustering for dynamic provision of uninterrupted efficient service.

Information, live demos, and endorsements about this release are available from [birt-exchange.com](http://birt-exchange.com) and [actuate.com](http://actuate.com). The Actuate site also makes "The Forrester Wave™: Open Source Business Intelligence (BI), Q3 2010" report freely available. The report recognizes Actuate and its value-added offerings for BIRT as a leader in Open Source Business Intelligence.




---

## About Actuate Java Component documentation





The printed and online documentation includes the materials described in Table I-1. You can obtain HTML and PDF files from [birt-exchange.com](http://birt-exchange.com) or [support.actuate.com](http://support.actuate.com).

Documentation updates are created in response to customer requirements and are available at both sites.

**Table I-1** Product documentation

For information about this topic	See the following resource
Installing and configuring Actuate Java Components	 <p><i>Installing an Actuate Java Component</i></p>
Late-breaking information and documentation updates	Release notes and updated localization, HTML help, and PDF files posted on <a href="http://birt-exchange.com">birt-exchange.com</a> and Actuate <a href="#">Support</a>
Introduction to report viewers BIRT Viewer Navigating, printing and exporting to other formats  BIRT Interactive Viewer Formatting reports, organizing data, working with charts, and hiding and filtering data	 <p><i>Working with Actuate BIRT Viewers</i></p>
Overview of BIRT Studio concepts Designing, editing, and formatting reports Organizing and filtering data, presenting data in a chart; inserting calculated data; functions and operators reference Creating and publishing report templates; configuring and customizing BIRT Studio pages	 <p><i>Using BIRT Studio - Java Component Edition</i></p>

**Table I-1** Product documentation

For information about this topic	See the following resource
Introduction to the Deployment Kit and Viewers, including concepts and online reporting Accessing files and folders; running reports	 <p><i>Using Actuate BIRT Java Components</i></p>
Overview of Java Component concepts and the web applications Using, customizing, and configuring Java Components Using the code components for JSPs, URL parameters, JavaScript files, Java servlets, Java Beans, and security facilities	 <p><i>Actuate Java Components Developer Guide</i></p>
Overview of concepts for programming with Actuate JavaScript Creating custom pages using Actuate JavaScript Reference of Actuate JavaScript classes and methods	 <p><i>Using Actuate JavaScript API</i></p>
Glossary	 <p><i>Actuate Glossary</i></p>

## Obtaining documentation

If you purchase the product, you can also download documentation using ftp as instructed in the e-mail from Actuate Distribution. If you select the typical setup when you install from the DVD, the installation creates the Actuate11\Manuals directory.

## Obtaining late-breaking information and documentation updates

The release notes contain late-breaking news about Actuate products and features. The release notes are available on the Actuate Support site at the following URL:

<http://support.actuate.com/documentation/releasenotes>

Updates to documentation in PDF form are available at the following URL:

<http://support.actuate.com/documentation>

If you are a new user, you must first register on the site and log in to view the release notes. [Birt-exchange.com](http://Birt-exchange.com) and [actuate.com](http://actuate.com) also provide product update information.

## Using PDF documentation

In each book, the table of contents and the index page numbers contain links to the corresponding topics in the text. In the table of contents, you access the link by positioning the pointer over the topic. In the index, you access the link by positioning the pointer over the page number.

The Actuate11 Manuals directory contains a file, master-index.pdx, which is an Adobe Acrobat Catalog utility that can search all the documents in the Actuate Manuals directory. This tool provides a convenient way to find information about a particular topic in Actuate documentation.

---

## About obtaining technical support

You can contact customer support by e-mail or telephone. For contact information, go to the following URL:

<http://www.actuate.com/services/support/contact-support.asp>

---

## About supported and obsolete products

The Actuate Support Lifecycle Policy and Supported Products Matrix are available on the Actuate e.Support web site. You can access the Support site at the following URL:

<http://support.actuate.com/documentation/spm>



---

## Typographical conventions

Table I-2 describes the typographical conventions in this document.

**Table I-2** Typographical conventions

Item	Convention	Example
Code examples	Monospace	Dim Text1 As String
File names	Initial capital letter, except where file names are case-sensitive	Detail.roi
Key combination	A + sign between keys means to press both keys at the same time	Ctrl+Shift
Menu items	Capitalized, no bold	File
Submenu items	Separated from the main menu item with a small arrow	File→New
User input or user response	Monospace	M*16*
User input in XML and Java code	Monospace italics	chkjava.exe <i>cab_name.cab</i>

---

## Syntax conventions

Table I-3 describes the symbols used to present syntax.

**Table I-3** Syntax conventions

Symbol	Description	Example
[ ]	Optional item	[Alias<alias name>]
	Array subscript	matrix[ ]
{ }	Groups two or more mutually exclusive options or arguments when used with a pipe	{While   Until}
	Defines array contents	{0, 1, 2, 3}
	Delimiter of code block	public ACJDesigner( ){ } <i>(continues)</i>

**Table I-3** Syntax conventions (continued)

Symbol	Description	Example
	Separates mutually exclusive options or arguments in a group	Exit {Do   For   Function   Sub}
	Java OR operator	int length   4
< >	Argument you must supply	<expression to format>
	Delimiter in XML	<xsd:sequence>

---

## About *Installing an Actuate Java Component*

*Installing an Actuate Java Component* includes the following chapters:

- *Introduction*. Provides an overview of this guide, a summary of Actuate Java Components documentation, and a list of the typographical conventions in this book.
- *Chapter 1. Before you begin*. Explains Java Components capabilities, installation prerequisites, and licensing.
- *Chapter 2. Deploying a Java Component*. Covers editing parameters for using Java Components and deploying the Java Components war file.
- *Chapter 3. Using a Java Component*. Describes testing, using, and licensing a Java Component.

# 1

## Before you begin

This chapter discusses the following topics:

- About Actuate Java Components
- About deployment formats
- Checking installation prerequisites
- About the license key file

---

## About Actuate Java Components

Actuate Java Components provide a complete reporting technology consisting of a report designer, report distribution in files and folders, and viewing or interactive viewing of reports. The following list describes each component:

- **BIRT Data Analyzer**  
A tool providing interactivity, such as displaying aggregate data values, filtering and sorting data, and pivoting axes, to a BIRT cross tab
- **BIRT Deployment Kit**  
A file and folder browser that optimizes performance and viewing of BIRT reports
- **BIRT Interactive Viewer**  
A viewer that you can use to customize and personalize a BIRT report to answer ad-hoc business questions
- **BIRT Spreadsheet Deployment Kit**  
A file and folder browser that optimizes performance and viewing of BIRT Spreadsheet reports
- **BIRT Studio**  
A web-based BIRT report designer for creating reports that can include charts and graphs
- **BIRT Viewer**  
A viewer for BIRT reports that extends the capabilities of BIRT to deliver rich dynamic content

---

## About deployment formats

You can install Java Components on Windows, Linux, and UNIX. Actuate provides Java Components in WAR and EAR formats. These formats are suitable for deployment on application servers shown in Table 1-1.

**Table 1-1** Java Component deployment formats

<b>File</b>	<b>Application server</b>
WL_TOMCAT_ ActuateBIRTJavaComponent.war	Apache Tomcat 6 BEA WebLogic 9.2 or 10.3
WAS_JBOSS_ ActuateBIRTJavaComponent.ear	JBoss 4.0.2 or 5.0 IBM WebSphere 6.1 or 1.1.01

Apache Tomcat 6 application server does not support EAR deployment. Only the JBoss and WebSphere application servers support EAR deployment.

---

## Checking installation prerequisites

Before you deploy a Java Component, ensure that your system meets the following requirements:

- Java Development Kit 5 or 6 (JDK)  
You need to use the JAR utility included in the JDK to decompress and compress the Java Components archive. Java Components also require the Java Runtime Environment (JRE) included in the JDK.
  - An application server  
Java Components run as a web application in the application server, such as Apache Tomcat 6 or JBoss 4.0.2 or 5.0.
  - Administrators group privileges on Windows, or root privileges on Linux or UNIX
  - Permission to start and stop the application server
- 

## About the license key file

You can download Java Components from BIRT-Exchange or you can download purchased products from an ftp site. You can also obtain the purchased products on media. Included in the download from BIRT-Exchange is an evaluation license for using each of the components for a limited time.

If you install products using the evaluation license, you do not need to reinstall before you activate the permanent license. To arrange for a permanent license key file, contact Actuate Customer Care at [customer care@actuate.com](mailto:customer care@actuate.com). If you are an international customer, your request routes to a team in international distribution. If you are not a direct Actuate customer, the partner or distributor who provides the product arranges for your license key file. The name for an Actuate Java Component license key file uses the following format:

```
Actuate_AJC_key_<ID>.xml
```

<ID> is a unique number generated by Actuate Licensing when it creates the license key file. You receive an e-mail that contains the permanent license key file information when Actuate processes your order.

If the license file does not exist, is invalid, or has expired, an error appears in the reportService log file, described later. When the license is invalid or expired, Java Components load, but any attempt to access an Actuate application, including the

login page, results in an error. If you have a problem with a license key file, contact Actuate Customer Care at [customer care@actuate.com](mailto:customer care@actuate.com).

# 2

## Deploying a Java Component

This chapter discusses the following topics:

- Editing the web.xml file
- Compressing files and renaming the WAR file
- Deploying the WAR file

---

## Editing the web.xml file

The first step in deploying the Java Component WAR file is editing the web.xml file. Extract web.xml from the WAR file, then edit web.xml to set configuration parameters for one or more components that you purchased or are evaluating. The tables in this section describe these parameters and actions you take. Perform these actions as you edit web.xml.

### How to edit web.xml


To access web.xml for editing, first decompress the WAR file that contains web.xml. Next, configure parameters for the Java Components that you want to use.

- 1 Create a directory named /temp. Java Components writes temporary files to this directory after deployment.
- 2 Decompress the ActuateJavaComponent.war file in a subdirectory of /temp. Type the following command:

```
jar -xf ActuateJavaComponent.war
```

Use this command on Windows, Linux, and UNIX. The Java Component files appear in the subdirectory of /temp.

Figure 2-1 shows these files on Linux.



```
# ls
ActuateJavaComponent.war  css                jsapisample       resources
ajclanding.jsp           filesfolders      landing.jsp        scriptlib
authenticate.jsp          help              login.jsp          swfs
birtAdapter              images            logout.jsp         viewer
bizRD                    portal            META-INF          WEB-INF
channels                  portal_welcome.xml  newrequest
checkactuate.jsp         iv                options
crossdomain.xml          js                requests
```

**Figure 2-1** Files extracted from ActuateJavaComponent.war

Keep all downloaded files together in their original relative locations.

- 3 Using a text editor that accepts UTF-8 encoding, edit web.xml in /WEB-INF to configure the parameters for the Java Components you purchased or are evaluating.
- 4 Save and close web.xml.



## Configuring locale parameters

The locale parameters, described in Table 2-1, are applicable to all Java Components.

**Table 2-1**      Locale parameters

Parameter name	Description	Action
DEFAULT_LOCALE	The value of this parameter determines the default locale. The default locale is en_US. Users can select a locale when they log in.	Use the default locale or a value from Localemap.xml in the WEB-INF directory.
DEFAULT_TIMEZONE	The value of this parameter determines the default time zone. The default time zone is Pacific Standard Time (PST).	Use the default time zone or a value from Timezonemap.xml in the WEB-INF directory.

## Configuring parameters for Deployment Kit

The components for BIRT Deployment Kit and BIRT Spreadsheet Deployment Kit have additional core configuration parameters in web.xml. Table 2-2 describes these parameters. Update these parameters before deployment.

For BIRT Deployment Kit, also review the parameters described in Table 2-3.

**Table 2-2**      Deployment Kit parameters

Parameter name	Description	Action
LOG_FILE_LOCATION	The location of the files that log Deployment Kit activities.	You must create this physical location on the file system. The default value is /logs.
TEMP_FOLDER_LOCATION	The location where Deployment Kit creates temporary files.	You must create this physical location on the file system. There is no default value.
TRANSIENT_STORE_PATH	Another location where Deployment Kit creates temporary files.	You must create this physical location on the file system. The default value is /temp.

## Configuring parameters for BIRT Viewer and BIRT Interactive Viewer

The BIRT Viewer and BIRT Interactive Viewer components also have core configuration parameters in web.xml. Table 2-3 describes these configuration parameters. Consider changing these parameters to optimize performance or to relocate log files.

**Table 2-3** BIRT Viewer parameters

Parameter name	Description	Action
BIRT_ARCHIVE_MEMORY_TOTALSIZE	Total memory available for BIRT report document files in kilobytes. The default value is 50 MB.	None required
BIRT_VIEWER_LOG_DIR	Location of the files that log BIRT viewer activity.	None required
REPOSITORY_CACHE_TIMEOUT_SEC	Length of time in seconds for retaining temporary files that BIRT Viewer creates when a user modifies the appearance of a report. The default value is 900, which is 15 minutes.	None required

## Configuring parameters for BIRT Studio

BIRT Studio component has one configuration parameter, shown in Table 2-4. Edit the parameter to change the path to BIRT resources. BIRT resources include libraries and templates for Actuate BIRT report designs and Actuate BIRT Studio.

**Table 2-4** BIRT Studio parameter

Parameter name	Description	Action
BIRT_RESOURCE_PATH	Path to Actuate BIRT shared resources. The default value is the following directory: <code>&lt;Tomcat install directory&gt; /webapps/newJavaComponent /resources</code>	None required

---

## Compressing files and renaming the WAR file

After editing the `web.xml` file, compress and rename the archive. For example, rename the archive `newJavaComponent.war`. Compress the files into a WAR file of a different name to preserve your original WAR file.

### How to compress files and rename the WAR file

- 1 After editing `web.xml` in the `WEB-INF` directory, move up one directory.
- 2 Check that files shown in Figure 2-1 are present in your current directory.
- 3 Compress the files and specify a new name for the WAR file. Type the following command:

```
jar -cf newJavaComponent.war *
```

Use this command on Windows, Linux, and UNIX. The WAR file containing the modified configuration values in `web.xml` appears.

---

## Deploying the WAR file

This section discusses deploying a Java Component WAR file. For example purposes, deployment on Tomcat 6 is shown.

To deploy the WAR file on an application server other than Tomcat 6, use your application server's deployment tools. If your application server does not have deployment tools, add the Java Components context root to your application server. Typically, you modify the application server's configuration file.

Perform the steps in the following procedure to deploy the WAR file by putting it in the `/webapps` directory.

### Deploying the WAR file on Apache Tomcat

- 1 Stop the Apache Tomcat service.
- 2 Copy the renamed Java Component WAR file from the working directory to the `/webapps` directory of your Tomcat installation files, as shown in Figure 2-2.

```
ajclanding.jsp          crossdomain.xml  iportal_welcome.xml  login.jsp          requests
authenticate.jsp       css              iv                    logout.jsp         resources
birtAdapter            filesfolders    js                    META-INF          scriptlib
bizRD                  help            jsapisample          newJavaComponent.war  swfs
channels              images          landing.jsp           newrequest         viewer
```

```
# cp newJavaComponent.war /var/lib/tomcat6.0/webapps
# cd /var/lib/tomcat6.0/webapps
#
```

**Figure 2-2** Copying the WAR file to /webapps on Linux

### 3 Start Tomcat.

The Tomcat log confirms the deployment of the WAR file and the location of the /temp directory that you created earlier.

Figure 2-3 shows an example of a Tomcat log file on Linux.

```
# cd /usr/share/tomcat6/logs
# tail catalina.out
Mar 8, 2009 10:59:30 AM org.apache.catalina.core.StandardEngine start
INFO: Starting Servlet Engine: Apache Tomcat/6.0.29
Mar 8, 2009 10:59:30 AM org.apache.catalina.core.StandardHost start
INFO: XML validation disabled
Mar 8, 2009 10:59:30 AM org.apache.catalina.startup.HostConfig deployWAR
INFO: Deploying web application archive newJavaComponent.war
- Initialising logging mechanism
- Writing logs to /usr/share/tomcat6/webapps/newJavaComponent/logs
- Enabling logging mechanism
- Temp files will be saved to : /opt/temp
#
```

Default Linux path to log

Deployment confirmation

Your temp directory

**Figure 2-3** Tomcat log file confirms deployment

# Using a Java Component

This chapter discusses the following topics:


- Testing the installation
- Using Java Components
- Licensing a Java Component in a WAR file
- Setting JVM properties

---

## Testing the installation

To test the Java Component install, open the Java Components landing page. Go to the following URL to access the landing page shown in Figure 3-1:

```
http://host:8080/newJavaComponent/ajclanding.jsp?
userid=anonymous
```



**Figure 3-1** Actuate Java Components landing page

---


## Using Java Components

If you are evaluating Java Components, use all products for the evaluation period. If you purchased particular Java Components, you can use only those products.

### Using BIRT Viewer and BIRT Interactive Viewer

BIRT Viewer is the default viewer that BIRT uses when you open a report. To use BIRT Interactive Viewer, open a report, and choose Enable Interactivity.

Figure 3-2 shows Enable Interactivity.




**Figure 3-2** Choosing Enable Interactivity

## Using BIRT Studio

Launch BIRT Studio by going to the following URL:

<http://host:8080/newJavaComponent/wr?&iportal>

Figure 3-3 shows the BIRT Studio opening page.




**Figure 3-3** Launching the BIRT Studio Component

## Using the Deployment Kits

Launch BIRT Deployment Kit and BIRT Spreadsheet Deployment Kit from the Actuate Java Components landing page.

### How to launch BIRT Deployment Kit


- 1 On the landing page, choose Actuate BIRT Deployment Kit, as shown in Figure 3-4.



Deployment Kit

**Figure 3-4** Actuate Java Components landing page

The Actuate BIRT Deployment Kit appears, as shown in Figure 3-5.




Launch BIRT Deployment Kit

**Figure 3-5** Launching the Actuate BIRT Deployment

- 2 Launch the Actuate BIRT Deployment Kit. Figure 3-6 shows the folders of report documents that you can browse.





**Figure 3-6** Accessing folders of report documents

## Licensing a Java Component in a WAR file

Included in the download from BIRT-Exchange is an evaluation license for using each of the components for a limited time. After installation, check the evaluation license expiration date by opening the reportService log in the following directory:

`<Tomcat install directory>/webapps/newJavaComponent/logs`

Figure 3-7 shows the reportService log on Windows.

```

Jan 30, 2011 12:54:51 PM com.actuate.portal.license.LicenseManager Initialize
SEVERE: ***** Actuate Java Component License Information *****
License Type: CPUBased
Usage Type: Beta
License ID: 3
IsDevelopment: true
IsNodeLocked: false
CPU Limit: unlimited
Major Release: 11
ServicePack: 1
Mode: workgroup
Expiration Date: wed Sep 15 00:00:00 PDT 2011

Supported options: Spread BIRTReport BIRTInteractiveviewer BIRTReportStudio DeploymentKit
Non-Supported Options:
Jan 30, 2011 12:54:51 PM com.actuate.reportcast.servlets.StartupServlet startJREM
  
```

**Figure 3-7** Checking the license expiration date and supported options

When you complete the evaluation, replace the evaluation license with a permanent license. After obtaining a new license key file, as explained earlier, perform the steps in the following procedure:

### How to license a Java Component

- 1 Rename the Java Component license file that Actuate sent you to `ajclicense.xml`.
- 2 Decompress the Java Component WAR file.

```
jar -xf ActuateJavaComponent.war
```

The Java Component files appear.

- 3 Copy the ajcllicense.xml file into the extracted <context root>\WEB-INF directory. For example, assuming you named the file newJavaComponent.war, the path to access the WEB-INF directory is:

```
<Tomcat install directory>/webapps/newJavaComponent/WEB-INF
```

- 4 Assuming WEB-INF is your current directory, move up one directory and type the following command on Windows, Linux, or UNIX:

```
jar -cf MyJavaComponent.war *
```

This command creates MyJavaComponent.war. This WAR file contains the license. The WAR file now has the context root MyJavaComponent.

- 5 Deploy MyJavaComponent.war to the application server or servlet engine as an application, as described earlier.
- 6 Restart the application server or servlet engine.

---

## Setting JVM properties

Deploying Actuate Java Components within some application server environments can result in the Java Virtual Machine (JVM) reporting PermGen space errors. If an error occurs, Actuate recommends setting the following JVM properties:

- Initial heap size  
Include -Xms64m as a Java option.
- Maximum heap size  
Include -Xmx512 as a Java option.
- Maximum size for the permanent generation heap  
Include -XX:MaxPermSize=128m as an option.

### How to configure JVM properties for Tomcat on Windows

- 1 Navigate to the following directory:  

```
<Tomcat install directory>\bin
```
- 2 Open catalina.bat.
- 3 Add -Xms64m -Xmx512 and -XX:MaxPermSize=128m to the JAVA\_OPTS variable specification.
- 4 Save and close catalina.bat.
- 5 Restart Tomcat.

### **How to configure JVM properties for JBoss on Windows**

- 1 Navigate to the following directory:

```
<JBoss install directory>\bin
```

- 2 Open run.bat.
- 3 Add -Xms64m -Xmx512 and -XX:MaxPermSize=128m to the JAVA\_OPTS variable specification.
- 4 Save and close run.bat.
- 5 Restart Tomcat.

### **How to configure JVM properties for Tomcat on Linux**

- 1 Navigate to the following directory:

```
/etc/tomcat6
```

- 2 Open tomcat6.conf.
- 3 Add -XMs64m -XMx512 and -XX:MaxPermSize=128m to the JAVA\_OPTS variable specification.
- 4 Save and close tomcat6.conf.
- 5 Restart Tomcat.



# Index

## A

accessing  
    customer support vi  
activity logs 7, 8  
ActuateJavaComponent.ear 2  
ajclicense.xml file 16  
application servers. *See* servers

## B

BIRT Data Analyzer 2  
BIRT Interactive Viewer 2, 8  
BIRT reports 8  
BIRT Studio 2, 8  
BIRT Viewer 2, 8  
BIRT\_ARCHIVE\_MEMORY\_TOTALSIZE  
    parameter 8  
BIRT\_RESOURCE\_PATH parameter 8  
BIRT\_VIEWER\_LOG\_DIR parameter 8

## C

cache 8  
changing  
    default locales 7  
    licensing options 3  
    time zones 7  
configuration parameters 7, 8  
configuring  
    application servers 16  
    Java Components 7–8  
context root 16  
context roots 9  
current release iv  
Customer Care 4  
customer support vi  
customizing WAR files 9

## D

decompressing WAR files 15  
DEFAULT\_LOCALE parameter 7  
DEFAULT\_TIMEZONE parameter 7  
deploying Java Components 2, 3, 9

Deployment Kit for BIRT Reports 2, 7  
Deployment Kit for Spreadsheet Reports 2, 7  
deployment tools 9  
designs 8  
document files 8  
documentation iii, v, vii  
downloading Actuate documentation v

## E

editors 6  
expired license keys 3

## F

file names 16  
files 3, 15

## H

HTML documentation. *See* documentation

## I

installation guide viii  
installing Java Components 12  
international licensing requests 3  
invalid license keys 3

## J

jar utility 16  
Java Components  
    configuring 7–8  
    deploying 2, 3  
    installing 12  
    obtaining licenses for 3

## L

libraries 8  
license key files 3  
license keys 3  
Localemap.xml 7  
locales 7  
log files 7, 8  
LOG\_FILE\_LOCATION parameter 7

## M

manuals. *See* documentation  
Manuals directory v, vi  
master-index.pdx vi  
memory 8

## N

naming WAR files 16

## O

online documentation. *See* documentation

## P

parameters. *See* configuration parameters  
PDF documentation vi  
*See also* documentation  
product updates vi

## R

release notes iv, vi  
report designs 8  
report document files 8  
reporting applications. *See* applications  
reports 8  
REPOSITORY\_CACHE\_TIMEOUT\_SEC  
parameter 8  
rich internet applications  
*See also* applications

## S

searching Actuate documentation vi

servers

configuring 16  
deploying Java Components to 9  
setting context root for 16  
servlet engines 16  
Support Lifecycle Policy vi  
Supported Products Matrix vi

## T

technical support vi  
TEMP\_FOLDER\_LOCATION parameter 7  
templates 8  
temporary files 7, 8  
testing Java Components installations 12  
text editors 6  
time zones 7  
Timezonemap.xml 7  
TRANSIENT\_STORE\_PATH parameter 7

## U

updates vi  
URLs 13, 16

## V

viewer activity logs 8

## W

WAR files 9  
web applications. *See* applications  
web archive files. *See* WAR files  
web servers. *See* servers  
web.xml 6